### **ARQ100**







Perfil vertical Wall profile

> 15mm 11mm

Perfil de vedação Floor profile








Aplicação a 8mm do rebordo da base. Application 8mm edge of the base.


**ITALB©X**®

## Tipologias Typologies

Porta direi Right door



# Porta esquerda Left door



# Foscagem Sandblasting

























#### Brass fittings.

8mm tempered glass.

Anodised chromed gloss-finish aluminium profiles.

Glass standard height: 2000mm.


Translucent PVC retaining membrane as sealing profile.

Additional height of the fixation system (+30mm). Clear reversible glass.

Specify exact dimensions on the order.

Other dimensions only on request.

#### **Medidas Standard**



Por defeito, sem indicação prévia, a porta

(P) terá 700mm. As default, without further information, the door (P) will have 700mm width.

O cliente deve fornecer a dimensão "L", resultante da medição da parede até à

face exterior da base. The client should provide the "L" dimension

# Aferição de medidas



base







eficácia na aplicação effectiveness of instalation



#### Foscagem com tratamento anti-manchas

Anti-stain treatment for sandblasting glass



Por medida

Custom-made



Vidro 8mm 8mm glass



Tratamento anticalcário Anti calcium treatment

### Compensação angular

Adjustments

shower trav



As medidas fornecidas devem ser resultantes da medição entre paredes.

#### Compensações feitas a cargo da ITALBOX.

The provided dimensions should be measured in between the walls.

Adjustments made by ITALBOX.





Portas de abrir Hinged door